

# STI Wireless Receivers

*Home & Work Series*



STI-34104



STI-34108



STI-34098



STI-34188



STI-V34104

## PRODUCT OVERVIEW

The receivers allow you to monitor up to 8 different STI wireless alert devices at a single, convenient location. Supervised for low battery and signal reception, they have an audible chime tone or 12 VDC output for siren. The 4-Channel Voice Receiver sounds a tune or a prerecorded programmable voice message. Offers ten tones/tunes or 53 selectable words (English or Spanish) to create a custom message up to four words. The 8-Channel Receiver offers a mirror function that can work with up to four additional 8-Channel Receivers. Devices can be latching or momentary by zone. STI offers multiple wireless products designed to alert you of several different conditions (such as: an open garage door, mail delivered, a car in the driveway, open exit door, removed fire extinguisher or activated push button, etc.).

## HOW IT WORKS

The receivers (excludes Single Channel Slave) supervise transmitter battery and signal reception (low battery is indicated with a short beep between 12 and 24 hours of detection).

## FEATURES

- Monitor 4 or 8 devices at a single, convenient location.
- Supervised for low battery and signal reception.
- Operates up to 1000' (line of sight), 433MHz.
- Audible chime tone and 12 volt output.
- Devices can be latching or momentary by each zone. (STI-V34104 & STI-34108)
- Includes 12 volt power supply.
- **STI-34104**
  - \* Monitors up to 4 devices.
  - \* Distinct beep and tone for each of the four devices.
  - \* Latching memory LED (flashes until reset).
  - \* Input power is 12 volt, 75mA.
- **STI-V34104**
  - \* Monitors up to 4 devices.
  - \* Ten tones/tunes or 53 selectable words (English or Spanish).
  - \* Words can be programmed in sets of up to four to create custom message.
- **STI-34108**
  - \* Monitors up to 8 devices with 8 zone LED indicators.
  - \* Mirror function (works with up to 4 additional 8-Channel Receivers).
  - \* Dual antennas for increased signal strength.
  - \* Form "C" contact for remote monitoring.
  - \* 300mA, 12 volt available for siren output (with 500mA, 12 volt supply).
  - \* Measures 5 ¼ x 5 ¾ x 1 ¼".
  - \* Key fob available for alert or on/off.
- **STI-34098**
  - \* Allows transmitters to connect to control panel.
- **STI-34188**
  - \* 8-Zone Relay Board for STI-34108.
  - \* 8 momentary Form "C" relay contacts rated 3A, 125 VAC, 3A 28VDC.

# STI Wireless Receivers

Dimensions and Technical Information

## MODELS AVAILABLE

### Receivers

|            |                               |
|------------|-------------------------------|
| STI-34104  | 4-Channel Receiver            |
| STI-34108  | 8-Channel Receiver            |
| STI-V34104 | 4-Channel Voice Receiver      |
| STI-34098  | Single Channel Slave Receiver |

### Sensors

|             |   |
|-------------|---|
| STI-34101   | Wireless Driveway Monitor Sensor (solar powered)                        |
| STI-34151   | Wireless Driveway Monitor Sensor (battery powered)                      |
| STI-34201   | Wireless Mailbox Alert Sensor   |
| STI-34301   | Wireless Garage Sentry Alert Sensor                                     |
| STI-34401   | Wireless Universal Alert Sensor   |
| STI-34451   | Wireless Door Chime Sensor  |
| STI-34601   | Wireless Doorbell Button Alert Sensor                                   |
| STI-34701   | Wireless Indoor Motion Detector Alert Sensor                            |
| STI-34752   | Wireless Outdoor Motion Detector Alert Sensor                           |
| STI-6200WIR | Wireless Fire Extinguisher Theft Stopper® Sensor                        |
| STI-6400WIR | Wireless Exit Stopper® Door Alarm Sensor                                |
| STI-6517B   | Wireless Stopper® Station Shield with Sound and<br>Wireless Transmitter |

### 4-Channel Receiver Kits

|           |   |
|-----------|---|
| STI-34100 | Wireless Driveway Monitor (solar powered)   |
| STI-34150 | Wireless Driveway Monitor (battery powered) |
| STI-34200 | Wireless Mailbox Alert                      |
| STI-34300 | Wireless Garage Sentry Alert                |
| STI-34400 | Wireless Universal Alert                    |
| STI-34450 | Wireless Door Chime                         |
| STI-34600 | Wireless Doorbell Button Alert              |
| STI-34700 | Wireless Indoor Motion Detector Alert       |

### Single Channel Slave Receiver Kits

|           |   |
|-----------|---|
| STI-34119 | Wireless Driveway Monitor (solar powered)   |
| STI-34159 | Wireless Driveway Monitor (battery powered) |
| STI-34209 | Wireless Mailbox Alert                      |
| STI-34309 | Wireless Garage Sentry® Alert               |
| STI-34409 | Wireless Universal Alert                    |
| STI-34609 | Wireless Doorbell Button Alert              |
| STI-34709 | Wireless Indoor Motion Detector Alert       |
| STI-34759 | Wireless Outdoor Motion Detector Alert      |

## APPROVALS

### TESTING

- STI-34104, STI-34108, STI-V34104
- CE
  - FCC & IC Compliant

### 4-Channel Voice Receiver Kits

|            |   |
|------------|---|
| STI-V34100 | Wireless Driveway Monitor (solar powered)   |
| STI-V34150 | Wireless Driveway Monitor (battery powered) |
| STI-V34200 | Wireless Mailbox Alert                      |
| STI-V34300 | Wireless Garage Sentry Alert                |
| STI-V34400 | Wireless Universal Alert                    |
| STI-V34450 | Wireless Door Chime                         |
| STI-V34600 | Wireless Doorbell Button Alert              |
| STI-V34700 | Wireless Indoor Motion Detector Alert       |
| STI-V34760 | Wireless Outdoor Motion Detector Alert      |

### Accessories

|           |  |
|-----------|--|
| STI-34099 | Single Channel Slave Receiver Case               |
| STI-34105 | Voltamax 12 VDC (500mA) power supply             |
| STI-30104 | Lamp Controller                                  |
| STI-30105 | Extended antenna                                 |
| STI-34106 | Key Fob  |
| STI-34109 | Repeater - Extends Transmitter range up to 1000' |
| STI-34188 | 8-Zone Relay Board for STI-34108                 |



**Safety Technology  
International, Inc.**

2306 Airport Road  
Waterford, Michigan  
48327, USA

Tel: 248-673-9898  
Fax: 248-673-1246  
Toll-free: 800-888-4784  
info@sti-usa.com  
www.sti-usa.com

Unit 49G Pipers Road  
Park Farm Industrial Estate  
Redditch, Worcestershire  
B98 0HU England

Tel: 44 (0) 1527 520 999  
Fax: 44 (0) 1527 501 999  
Free: 0800 085 1678 (UK)  
www.sti-europe.com